ADDICRETE T



DESCRIPTION

ADDICRETE T is a safe additive designed to control the release of salts from concrete products, greatly increasing their market appeal and durability. ADDICRETE T reacts with soluble salts in the cement-aggregate matrix and prevents them from migrating as soluble salts to the surfaces of finished products. ADDICRETE T also acts as a cement and colour dispersion agent in the concrete wet mix as well as a water reducer.

APPLICATIONS

ADDICRETE T is used as an additive in the manufacture of cement masonry products such as concrete pavers, bricks and blocks. ADDICRETE T can also be used as an additive for renders, floats and premix concrete for slabs etc.

BENEFITS

- No unsightly chalking on finished products.
- Improved aesthetics, brighter, even colours.
- Improved structural integrity of products, better strength and abrasion resistance.
- One product for colour and cement dispersion and efflorescence control. No secondary additives needed.
- Minimal cost per mix.
- Has the ability to reduce cement in mixes whilst increasing strength and abrasion of finished products.

PRODUCT USAGE

WET MIX PAVING

As a guide, 350 - 700 grams of ADDICRETE T is added per 100kg of cement. Depending on water/cement ratios and cement-aggregate ratios, the ADDICRETE T quantity can be increased or decreased depending on the amount of lubricity required.

DRY MIX PAVING

As a guide, 350 - 700 grams of ADDICRETE T is added per 100kg of cement. Depending on water-cement ratios and cement-aggregate ratios, the ADDICRETE T quantity can be increased or decreased depending on the amount of lubricity required.

SAND FINISH RENDER

As a guide, 20-30 grams of ADDICRETE T is added per 20kg bag cement based on a 1:4 cement/sand render. Half the normal water should be added to the mix prior to adding ADDICRETE T. Let mix, then add water to achieve the desired slump.

SAND/CEMENT FLOATS

As a guide, 20-30 grams of ADDICRETE T is added per 20kg of cement based on a 1:5-6 cement/sand render. Half the normal water should be added to the mix prior to adding ADDICRETE T. Let mix, then add water to achieve the desired slump.

STORAGE

Store ADDICRETE T in sealed containers under cover in a cool area away from foodstuffs.

CLEAN UP

Clean up ADDICRETE T with absorbent material and dispose of according to state and federal laws.

PACK SIZES

ADDICRETE T is sold in packs of 18kg, 180kg and 900kg.

FACTORY 16 GOONGARRIE STREET BAYSWATER WA 6053 AUSTRALIA POSTAL PO BOX 385 BAYSWATER WA 6933 AUSTRALIA

TELEPHONE TEL. (08) 9378 2022 FAX. (08) 9377 2575 MOB. 0418 956 860 IDENTIFICATION PAGE **1** of **2** ISSUE: JULY 2011 REF: ADDP

ADDICRETE T



TRANSPORT

ADDICRETE T is not a hazardous product for transport under the guidelines of WORKSAFE AUSTRALIA.