

ATTAFLEX



DESCRIPTION

ATTAFLEX is based on a resilient, tough, pure acrylic resin emulsion with wet adhesion incorporating a specialized chemically inert filler system with crosslinking properties. **ATTAFLEX** has a degree of flexibility. The combined properties make an excellent resilient membrane coating. **ATTAFLEX** is supplied in various colours.

FEATURES

- **ATTAFLEX** is suitable for application to concrete, steel, aluminium, bricks, timber, bitumen and in many cases several plastics. **ATTAFLEX** is used with sealer in most cases.
- **ATTAFLEX** has very good resistance to chemicals and oils.
- **ATTAFLEX** is a 'membrane' coating which has an excellent degree of flexibility with toughness.
- **ATTAFLEX** can be applied in thick layers eg 1mm (1m²/litre) as a three-coat application
- **ATTAFLEX** can withstand being under water.
- **ATTAFLEX** with attritive resistance aggregates, has anti slip properties which can stand a high degree of wear.
- **ATTAFLEX** in its wet state is cleaned up with water.

APPLICATIONS

- Waterproof membrane coating.
- Decorative and trafficable coating for cobble paving, driveways, service areas, patios, swimming pool surrounds and factory floors and walls.
- Work boat deck coating.
- Insulating coating for metal buildings.
- **ATTAFLEX** coloured is used where a smooth finish coating is required for the application.

DIRECTIONS

Prepare all types of surfaces so they are clean, free of oil, dust, laitance and chalky paint respectively. Painted surfaces must be well bound and strongly adhered to the under surface. The paint film must not be chalky or defective. Unpainted surfaces must be integrally bound to the substrate it is on.

Porous Surfaces: Concrete, bricks, timber bitumen seal with **TUFSEAL**. Coverage 8-10m²/litre.

Non-Porous Surfaces: Painted surfaces seal with **TUFSEAL** 8-10m²/litre. Concrete seal with **SCREEDBOND**/cement combination as a slurry screed 1L **SCREEDBOND** to 1L GP cement when mixed covers 4m² seal with **CORROPEL**.

If the surface of the substrate is in good condition and not pitted or rusted apply the **ATTAFLEX** direct to the cleaned surface. For old, pitted and rusted substrates seal with a rust preventative coating (**CORROPEL**).

APPLICATIONS

ATTAFLEX for anti-slip, waterproofing, decks, factory floors: apply by roller, brush or hopper spray at the rate of 2-3m²/litre per coat. Two coats are recommended for hard use areas.

ATTAFLEX for driveways, cobble paving, walls: apply at the rate 8-10m²/litre per coat. Two or three coats may be necessary depending on the state of the surface and degree of use.

ATTAFLEX for a stone damage barrier, insulating or sound proofing: apply by roller, trowel or hopper spray at the rate of 1m²/litre per coat. Two coats are recommended for these applications.

Allow each coat to dry (for example 2 hours) before applying the next coat.

FACTORY
16 GOONGARRIE STREET
BAYSWATER WA 6053
AUSTRALIA

POSTAL
PO BOX 385
BAYSWATER WA 6933
AUSTRALIA

TELEPHONE
TEL. (08) 9378 2022
FAX. (08) 9279 7978
MOB. 0408 940 669

IDENTIFICATION
PAGE 1 of 2
ISSUE: JULY 2015
REF: ATFX

QUINDALUP HOLDINGS PTY LTD (A.C.N. 009 026 386) AS TRUSTEE FOR CALMARC FAMILY TRUST (ABN 18 340 289 669)

This information is offered solely for the customer and/or specifier for their consideration, investigation and verification. The suggestions mentioned herein should be fully assessed prior to application. No warranty or implied liability is given for any recommendations, advice, suggestions made by Calmarc Chemicals or representatives, agents or distributors for the conditions of use and labour for the products which are beyond our control. Catalogue or specification contents may change from time to time without notice. S.D.S. is available.

ATTAFLEX



NOTE: A seal coat of **TUFSEAL** or **CALSEAL** (colour matched or clear) is recommended to be applied on top of the **ATTAFLEX** finishes. These sealers enhance and add further protection with the **ATTAFLEX** coating. Apply the sealer at a rate of 10-12m²/litre. Clean up with water.

CLEAN UP

Clean wet **ATTAFLEX** with water. For set **ATTAFLEX**, clean off with **MARCMOVE** or **WIZSTRIP**.

STORAGE

Store **ATTAFLEX** in sealed containers in a cool area between 5-30°C and away from foodstuffs.

SAFETY

Wear protective clothing, safety boots and goggles. For skin contact, wash off **ATTAFLEX** with soapy water. For eye contact, rinse the eyes with water for 15 minutes and seek medical advice.

PACK SIZES

ATTAFLEX is sold in packs of 5, 10, 15, 20 and 200 litres.

TRANSPORT

ATTAFLEX is not a hazardous good as defined by SAFE WORK AUSTRALIA.

FACTORY
16 GOONGARRIE STREET
BAYSWATER WA 6053
AUSTRALIA

POSTAL
PO BOX 385
BAYSWATER WA 6933
AUSTRALIA

TELEPHONE
TEL. (08) 9378 2022
FAX. (08) 9279 7978
MOB. 0408 940 669

IDENTIFICATION
PAGE 2 of 2
ISSUE: JULY 2015
REF: ATFX

QUINDALUP HOLDINGS PTY LTD (A.C.N. 009 026 386) AS TRUSTEE FOR CALMARC FAMILY TRUST (ABN 18 340 289 669)

This information is offered solely for the customer and/or specifier for their consideration, investigation and verification. The suggestions mentioned herein should be fully assessed prior to application. No warranty or implied liability is given for any recommendations, advice, suggestions made by Calmarc Chemicals or representatives, agents or distributors for the conditions of use and labour for the products which are beyond our control. Catalogue or specification contents may change from time to time without notice. S.D.S. is available.