

ELASTATAK



DESCRIPTION

ELASTATAK is a compound of selected blends of acrylic polymers in a waterborne emulsion. The dried film has cohesive elastic properties with high adhesion. **ELASTATAK** is able to cushion differential movement of an under and upper substrate when **ELASTATAK** is in between as a bonding medium.

APPLICATIONS

- **ELASTATAK** is applied onto surfaces that have been painted or primed with **GENPRIME**. **ELASTATAK** (due to its elastic properties) in most cases compensates for differential movement between the old paint and a new coating or substrate applied onto the **ELASTATAK**.
- **ELASTATAK** is an excellent, flexible sealer for timber.
- **ELASTATAK** is also used for sealing powdery white roofs before roof coating. This is necessary due to the oily nature of the white pigments in the roof tiles.

DIRECTIONS

FOR PAINTED SHEET IRON – GALVANISED OR COLORBOND:

Clean the old painted surface with a high-pressure water spray. Follow by water rinsing and scrubbing. Allow the surface to dry. Remove any old curled paint. Apply a coat of **ELASTATAK** onto the old painted surface at the rate of 8-10m²/litre. Allow **ELASTATAK** to dry for a minimum of 4 hours at 25°C before applying finishing coatings, e.g. TUFSEAL or **FLEXITEX** as directed.

FOR TIMBER OR CHIPBOARD:

Apply one coat of **ELASTATAK** at 6-8m²/litre. Allow **ELASTATAK** to dry for a minimum of 4 hours at 25°C before applying elastomeric topcoats (**MEMFLEX** or **FLEXITEX**).

BONDING SCREEDS AND RENDERS TO WELL BONDED, PAINTED WALLS:

High pressure water blast (min 2500psi) walls to remove any loose paint, allow to dry thoroughly for at least 3 days at 25°C. After drying, check for paint shrinkage delamination and remove unsound paint.

Apply two coats of **ELASTATAK** at 6-8m²/litre/coat. Allow each coat of **ELASTATAK** to dry for a minimum of 4 hours at 25°C.

Follow with a coat of **ELASTATAK** at the same rate after 24 hours or more. While **ELASTATAK** is wet, trowel on the screed or render with **SCREEDBOND** added to the render mix at 2 litres per 20 kg of cement. There will be limited suction, so the initial set of the render will be retarded.

BONDING PAINTS TO PAINTED, CRACKED INTERNAL AND EXTERNAL WALLS:

Apply one coat of **ELASTATAK** at 8m²/litre if the cracks are fine and small in number. Apply two coats if the cracks are of medium to high density in number.

Allow each coat of **ELASTATAK** to dry for a minimum of 4 hours at 25°C. Drying times are longer for temperatures lower than 25°C and a little shorter for higher temperatures.

The coloured top finish water borne wall paint has 1 litre of **ELASTATAK** added to 4 litres of this finish paint. Mix the **ELASTATAK** well into the coloured paint. Apply 2 coats as normal of this paint mixture.

FACTORY
16 GOONGARRIE STREET
BAYSWATER WA 6053
AUSTRALIA

POSTAL
PO BOX 385
BAYSWATER WA 6933
AUSTRALIA

TELEPHONE
TEL. (08) 9378 2022
FAX. (08) 9377 2575
MOB. 0408 940 669

IDENTIFICATION
PAGE 1 of 2
ISSUE: 15 JANUARY 2015
REF: ELTK

QUINDALUP HOLDINGS PTY LTD (A.C.N. 009 026 386) AS TRUSTEE FOR CALMARC FAMILY TRUST (ABN 18 340 289 669)

This information is offered solely for the customer and/or specifier for their consideration, investigation and verification. The suggestions mentioned herein should be fully assessed prior to application. No warranty or implied liability is given for any recommendations, advice, suggestions made by Calmarc Chemicals or representatives, agents or distributors for the conditions of use and labour for the products which are beyond our control. Catalogue or specification contents may change from time to time without notice. S.D.S. is available.

ELASTATAK



STORAGE

ELASTATAK should be stored in a covered, cool area. The lid should be replaced after use or after a quantity has been decanted from it.

CLEAN UP

Clean tools with water immediately after use. If **ELASTATAK** sets as a film, remove with **MARCMOVE** or **WIZSTRIP**.

PACK SIZES

ELASTATAK is sold in packs of 10, 15, 20 and 200 litres.

TRANSPORT

ELASTATAK is not a hazardous good as defined by Safe Work Australia.

NOTES

If walls have NOT been painted, a sealer must be applied prior to **ELASTATAK** application.

Surfaces that are chalky, powdery or friable are not recommended for **ELASTATAK** application unless sealed beforehand.

FACTORY
16 GOONGARRIE STREET
BAYSWATER WA 6053
AUSTRALIA

POSTAL
PO BOX 385
BAYSWATER WA 6933
AUSTRALIA

TELEPHONE
TEL. (08) 9378 2022
FAX. (08) 9377 2575
MOB. 0408 940 669

IDENTIFICATION
PAGE 2 of 2
ISSUE: 15 JANUARY 2015
REF: ELTK

QUINDALUP HOLDINGS PTY LTD (A.C.N. 009 026 386) AS TRUSTEE FOR CALMARC FAMILY TRUST (ABN 18 340 289 669)

This information is offered solely for the customer and/or specifier for their consideration, investigation and verification. The suggestions mentioned herein should be fully assessed prior to application. No warranty or implied liability is given for any recommendations, advice, suggestions made by Calmarc Chemicals or representatives, agents or distributors for the conditions of use and labour for the products which are beyond our control. Catalogue or specification contents may change from time to time without notice. S.D.S. is available.