

ULTRASEAL



DESCRIPTION

ULTRASEAL is based on a SOLVENT FREE, NON HAZARDOUS, very hard acrylic wax alloy emulsion polymer. It produces a water clear, HIGH GLOSS FINISH, which is resilient and tough. ULTRASEAL can be used on a multitude of surfaces that require a high gloss finish. ULTRASEAL has been designed specifically to produce a high gloss finish without the use of hazardous solvents for internal use.

APPLICATIONS

ULTRASEAL is suitable for sealing a variety of internal concrete substrates including old concrete floors.

ULTRASEAL is used as a sealer on ceramic substrates eg. terracotta tiles, slate, clay and concrete paving and honed concrete.

ULTRASEAL can be used externally if coloured. It is suitable for most types of mineral surfaces.

PREPARATION

Stir thoroughly before use.

BARE CONCRETE/CLAY/RECONSTITUTED: Any oil and grease should be removed with MARCMOVE before water blasting. The concrete should be free of dust, dirt, oil, mould, algae, fungi, laitance and should have a sound, firm surface which does not give way when given the packaging tape adhesion test. Allow the surface to dry thoroughly after water blasting with a high pressure machine. Allow the surface to dry thoroughly before applying the ULTRASEAL.

CERAMIC TILES: Make sure there is no grout scum on the surface of the tiles. If so, acid clean with DYNACLENE diluted up to 3 times with water. Treat as bare concrete as detailed above after the DYNACLENE acid clean. If the tiles are clean and

in very good condition, clean them with a vinegar/methylated spirits mixture and water. Rinse well with water, thoroughly dry tiles before sealing.

TIMBER: Prepare the surface of the timber so it is clean, free of dust, laitance oils, moulds and is dry. Apply ULTRASEAL with a low hair roller or pad in slow even strokes at low speed and minimum roller track to previous wet rolled coating.

Application of the second coat is done in a similar fashion to the first and is done when the first coat is fully dry.

Do not apply thicker application than the recommended rate to apply ULTRASEAL.

NOTICE:

Any acidic treatment to substrates must be neutralized with Neutra and rinsed with water.

Allow the substrate to dry thoroughly before applying the ULTRASEAL.

Do not apply under 16 degrees celsius.

APPLICATION RATES

SEAL COAT ON UNGLAZED TILES/SLATE: Apply two coats at 8-10m²/litre/coat.

PAINTED CONCRETE: Apply one or two coats at 8-10m²/litre.

CONCRETE PAVERS, RECONSTITUTED LIMESTONE PAVERS : Apply two coats at 8-10m²/litre/coat.

CLAY PAVERS: Apply two coats at 8-10m²/litre/coat.

EXPOSED AGGREGATE CONCRETE: Apply two coats at 6-8m²/litre/coat.

TIMBER: Apply two coats at 10-12m²/litre per coat.

Allow first coat to fully dry before application of a second coat. Drying is varied due to weather conditions and as a guide ULTRASEAL should be

FACTORY
16 GOONGARRIE STREET
BAYSWATER WA 6053
AUSTRALIA

POSTAL
PO BOX 385
BAYSWATER WA 6933
AUSTRALIA

TELEPHONE
TEL. (08) 9378 2022
FAX. (08) 9377 2575
MOB. 0418 956 860

IDENTIFICATION
PAGE 1 of 2
ISSUE: AUG8,2016
REF: XPFN

QUINDALUP HOLDINGS PTY LTD (A.C.N. 009 026 386) AS TRUSTEE FOR CALMARC FAMILY TRUST (ABN 18 340 289 669)

This information is offered solely for the customer and/or specifier for their consideration, investigation and verification. The suggestions mentioned herein should be fully assessed prior to application. No warranty or implied liability is given for any recommendations, advice, suggestions made by Calmarc Chemicals or representatives, agents or distributors for the conditions of use and labour for the products which are beyond our control. Catalogue or specification contents may change from time to time without notice. M.S.D.S. is available.

ULTRASEAL



allowed to dry for at least 4 hours between coats at 25°C-32°C. Under 25°C allow 12 hours to dry. The surface texture (roughness) and porosities will have an effect on the amount used for most substrates. Tests should be done to determine a spread rate. Avoid excess application of ULTRASEAL as excess application can make the surface slippery.

TRANSPORT

ULTRASEAL is not a hazardous product for transport under the guidelines of WORKSAFE AUSTRALIA.

NOTICE

NOTE : If applying ULTRASEAL by roller there could be a tendency to create air bubbles in the coating by too vigorous action in rolling; and over rolling on partially dried coating. Beware of this advice if rolling the ULTRASEAL. It is best to apply ULTRASEAL by Tee Bar Pad applicator, soft hair broom, brush or airless spray.

ULTRASEAL needs to be applied in thin even coats laying off during application. Thick coats cause drying problems with ULTRASEAL sometimes leaving an opalescent(whitish) film - not a clear film. Substantial water contact within a week or so after application may create a very light whitish spot effect in the film. The effect disappears when the water is removed or evaporated and will not occur when the film gains full strength. Rising moisture in substrates needs to be inhibited before application of ULTRASEAL. Recommended a sample be tried before proceeding.

CLEAN UP

Clean up wet ULTRASEAL deposits with water and dry ULTRASEAL deposits with MARCMOVE.

STORAGE

Store ULTRASEAL in sealed containers under cover in a cool area away from foodstuffs.

PACK SIZES

ULTRASEAL is sold in packs of 5, 10 and 20 litres.

FACTORY
16 GOONGARRIE STREET
BAYSWATER WA 6053
AUSTRALIA

POSTAL
PO BOX 385
BAYSWATER WA 6933
AUSTRALIA

TELEPHONE
TEL. (08) 9378 2022
FAX. (08) 9377 2575
MOB. 0418 956 860

IDENTIFICATION
PAGE 2 of 2
ISSUE: AUG8,2016
REF: XPFN

QUINDALUP HOLDINGS PTY LTD (A.C.N. 009 026 386) AS TRUSTEE FOR CALMARC FAMILY TRUST (ABN 18 340 289 669)
This information is offered solely for the customer and/or specifier for their consideration, investigation and verification. The suggestions mentioned herein should be fully assessed prior to application. No warranty or implied liability is given for any recommendations, advice, suggestions made by Calmarc Chemicals or representatives, agents or distributors for the conditions of use and labour for the products which are beyond our control. Catalogue or specification contents may change from time to time without notice. M.S.D.S. is available.