

# DAMP-PEL RTU



## DESCRIPTION

DAMP-PEL W is an aqueous emulsion concentrate which is used to make mineral building materials damp-proof and water repellent.

## APPLICATIONS

- Injection into building foundations at or below floor level to form a damp course.
- Making plasterboard repellent.
- Making fired clay and concrete products water repellent.

## DIRECTIONS

**WATER REPELLENT:** Apply two coats of DAMP-PEL W as a wet on wet application. Spread rate of dilution should be 3-4m<sup>2</sup> per litre per coat.

Drying time for water repellency application is 4 - 6 hours at 25 degrees celcius.

DAMP-PEL W should not be applied in rain or if inclement weather is expected within 72 hours.

## HANDLING & SAFETY

DAMP-PEL W should be keep away from glass or metals.

NOTE : A white deposit may form on the substrate surface if applied in excess.

## TRANSPORT

DAMP-PEL W is not classified as a dangerous or hazardous good under the guidelines of WorkSafe Australia.

FACTORY  
16 GOONGARRIE STREET  
BAYSWATER WA 6053  
AUSTRALIA

POSTAL  
PO BOX 385  
BAYSWATER WA 6933  
AUSTRALIA

TELEPHONE  
TEL. (08) 9378 2022  
FAX. (08) 9377 2575  
MOB. 0418 956 860

IDENTIFICATION  
PAGE 1 of 1  
ISSUE: JULY 2011  
REF: DMPL

QUINDALUP HOLDINGS PTY LTD (A.C.N. 009 026 386) AS TRUSTEE FOR CALMARC FAMILY TRUST (ABN 18 340 289 669)

This information is offered solely for the customer and/or specifier for their consideration, investigation and verification. The suggestions mentioned herein should be fully assessed prior to application. No warranty or implied liability is given for any recommendations, advice, suggestions made by Calmarc Chemicals or representatives, agents or distributors for the conditions of use and labour for the products which are beyond our control. Catalogue or specification contents may change from time to time without notice. M.S.D.S. is available.