DEMOULD



DESCRIPTION

DEMOULD is a water dilutable mould release agent for various types of moulding replication. DEMOULD is also used as an anti-stick agent for concrete truck shoots and areas where cement build up occurs.

DIRECTIONS

MOULD RELEASE AGENT

Apply DEMOULD by brush, roller or spray at an approximate rate of 18 - 20m²/litre. The film should be thin with no runs. It is advisable to spray the mould at least two hours before pouring. This allows DEMOULD to dry and establish before pouring cement mixes.

ANTI STICK AGENT

Apply DEMOULD by brush, roller or spray at an approximate rate of 8-10m²/litre. The film should be thin with no runs. Reapplication should occur daily or weekly. Tests should be carried out to evaluate suitability and reapplication rates.

All figures, spread rates and percentages are guides and tests should be performed to determine the correctness of the product for each individual use. In some cases, DEMOULD can be diluted with water for mould release but extensive testing is required before use.

CLEAN UP

Clean up is done with water.

STORAGE

Store DEMOULD in a cool area, between 5 - 300C under cover and away from any other chemicals, foodstuffs or items.

PACK SIZES

DEMOULD is sold in packs of 20 and 200 litres.

FACTORY 16 GOONGARRIE STREET BAYSWATER WA 6053 AUSTRALIA POSTAL PO BOX 385 BAYSWATER WA 6933 AUSTRALIA TELEPHONE TEL. (08) 9378 2022 FAX. (08) 9377 2575 MOB. 0418 956 860 IDENTIFICATION PAGE 1 of 1 ISSUE: JULY 2011 REF: DEMD

QUINDALUP HOLDINGS PTY LTD (A.C.N. 009 026 386) AS TRUSTEE FOR CALMARC FAMILY TRUST (ABN 18 340 289 669 This information is offered solely for the customer and/or specifier for their consideration, investigation and verification. The suggestions mentioned herein should be fully assessed prior to application. No warranty or implied liability is given for any recommendations, advice, suggestions made by Calmarc Chemicals or representatives, agents or distributors for the conditions of use and labour for the products which are beyond our control. Catalogue or specification contents may change from time to time without notice. M.S.D.S. is available.

TRANSPORT

DEMOULD is classified as a non-hazardous good for transport by Worksafe Australia.