

# SCREEDBOND



## DESCRIPTION

SCREEDBOND is a stabilised carboxylated synthetic rubber-acrylic elastomeric terpolymer waterborne liquid dispersion, which gives high bond strength and many other excellent qualities to mixes containing cement. It incorporates water retaining and reducing agents and dispersants. It has been formulated as a modifier for normal grey or white cement mixes.

## FEATURES

- Improves adhesion to many surfaces e.g. concrete, cement sheet, iron, tiles, bitumen, wood board and brickwork.
- Increases toughness, flexibility and resistance to heat ageing and movement caused by temperature differences.
- Gives excellent resistance against water and water vapour, salt penetration and improved protection against most chemicals except acids.
- SCREEDBOND cement mixes have good workability at low water cement ratios. SCREEDBOND cement can be applied in thin layers and diminishes dusting of the final concrete layer.

## USES

SCREEDBOND used with various ratios of cement/aggregate mixes have multiple uses in many situations and since the surface preparation and applications vary over a wide range the following list may assist users to select the most suitable product data sheet or sheets for their particular use or problem:

- Waterproofs renders and coatings for exterior or interior walls or surfaces e.g. concrete tanks, walls and floors.
- Damp courses.

- Industrial flooring, floor screeds and toppings for use in food factories, fertiliser factories/floors and cold rooms. It can be used to form stair nosing mixes.
- Patching and repairing concrete.
- Protects steel from corrosion.
- Repairs to concrete piles, jetties and sea walls.
- Excellent adhesive for polystyrene bead concrete insulation and for bonding gypsum hardwall plaster to concrete.
- Water-resistant adhesive for tiles and brick slips or an alternative to epoxy tile grouts in circumstances where there are no acids or solvents.
- Excellent anti-slip and anti-dusting coatings.
- Suitable for thin layer applications of screeds.

NOTE: Application guides for the various uses of SCREEDBOND modified cement mixes are provided separately.

## SCREEDBOND GENERAL NOTES

Mixing procedures for mortars and screeds containing SCREEDBOND are virtually the same as for conventional compositions. The amount of water is reduced in the region of 20%. The colour of cement mixes incorporating SCREEDBOND will be a little darker than normal cement mixes. The mixing cycle with SCREEDBOND/cement/aggregate mixes is about 75% of the time for conventional mixes.

It is recommended for high levels (3.5L/20 kg cement) of SCREEDBOND in a mix, use a propellor in a slow revolving drill at 500 - 1000rpm. Mixing is done in a 10 - 20 litre plastic bucket. For lower addition levels (1 - 2L/20 kg cement) of SCREEDBOND, in a mix, mixing can be done by propellor in a slow revolving drill or a cement mixer.

FACTORY  
16 GOONGARRIE STREET  
BAYSWATER WA 6053  
AUSTRALIA

POSTAL  
PO BOX 385  
BAYSWATER WA 6933  
AUSTRALIA

TELEPHONE  
TEL. (08) 9378 2022  
FAX. (08) 9377 2575  
MOB. 0418 956 860

IDENTIFICATION  
PAGE 1 of 2  
ISSUE: JULY 2011  
REF: SDBD

QUINDALUP HOLDINGS PTY LTD (A.C.N. 009 026 386) AS TRUSTEE FOR CALMARC FAMILY TRUST (ABN 18 340 289 669)  
This information is offered solely for the customer and/or specifier for their consideration, investigation and verification. The suggestions mentioned herein should be fully assessed prior to application. No warranty or implied liability is given for any recommendations, advice, suggestions made by Calmarc Chemicals or representatives, agents or distributors for the conditions of use and labour for the products which are beyond our control. Catalogue or specification contents may change from time to time without notice. M.S.D.S. is available.

# SCREEDBOND



Sharp clean aggregates and sands are recommended. They should be free of clay fines.

Aeration workability additives should NOT be used with SCREEDBOND. If hydrated lime or ground silicas are used in a mix, their use should be no more than an eighth part by volume (one twentieth part by weight) of the cement content in a cement: aggregate/sand mix.

All materials should be measured by weight if possible. If measuring materials by volume, ensure that they are well tamped in the measuring container.

## STORAGE

SCREEDBOND should be stored in a covered, cool area. The lid should be replaced after each use.

## CLEAN UP

Clean tools with water immediately after use. If SCREEDBOND hardens, remove with mineral turpentine or MARCMOVE.

## PACK SIZES

SCREEDBOND is sold in packs of 20, 200 litres.

## TRANSPORT

SCREEDBOND is not a hazardous good as defined by WorkSafe Australia.

FACTORY  
16 GOONGARRIE STREET  
BAYSWATER WA 6053  
AUSTRALIA

POSTAL  
PO BOX 385  
BAYSWATER WA 6933  
AUSTRALIA

TELEPHONE  
TEL. (08) 9378 2022  
FAX. (08) 9377 2575  
MOB. 0418 956 860

IDENTIFICATION  
PAGE 2 of 2  
ISSUE: JULY 2011  
REF: SDBD

QUINDALUP HOLDINGS PTY LTD (A.C.N. 009 026 386) AS TRUSTEE FOR CALMARC FAMILY TRUST (ABN 18 340 289 669)

This information is offered solely for the customer and/or specifier for their consideration, investigation and verification. The suggestions mentioned herein should be fully assessed prior to application. No warranty or implied liability is given for any recommendations, advice, suggestions made by Calmarc Chemicals or representatives, agents or distributors for the conditions of use and labour for the products which are beyond our control. Catalogue or specification contents may change from time to time without notice. M.S.D.S. is available.