

ACRABIT



DESCRIPTION

ACRABIT is a water based, high solids, flexible bitumen modified acrylic coating.

ACRABIT is especially effective for positive side waterproofing of planter boxes and retaining walls.

FEATURES

- **ACRABIT** is easy to apply with high build.
- **ACRABIT** is water based, low odour, nonflammable and nontoxic.
- **ACRABIT** is cold applied and cleans up with water.
- **ACRABIT** is microfibre reinforced, giving extra durability.
- **ACRABIT** has excellent elongation.
- **ACRABIT** has excellent impact resistance.

APPLICABLE SUBSTRATES

- Concrete: 28 days cured minimum.
- Cement/sand screeds, renders: 28 days and 14 days cured minimum respectively
- Masonry and concrete block work: voids filled, protrusions removed for a flat finish.
- Natural and Reconstituted limestone blockwork: voids filled, protrusions removed for a flat finish.

PREPARATION

All surfaces must be free of dirt, oil, grease, curing compounds or other contamination which may inhibit bond. Any loose material should be removed, and surfaces should be repaired if necessary, to provide a solid foundation. Porous substrates should be primed with **ACRABIT** diluted 1:1 with clean water. Substrates subject to hydrostatic moisture or insufficient curing time should be primed with **PLYCRETE**.

APPLICATION

ACRABIT should be applied by brush or roller at a rate of 1m²/L/coat. Two or three coats should be applied. Apply the first coat in one direction and the second coat at right angles to the first. Do not attempt to rework any partially set product. Allow 2-4 hours between coats at 25°C.

Dry in 24-48 hours after final coat at 25°C. Full cure in 7 days. Protective board or sheeting should be used to protect the membrane against by traffic or back fill.

ACRABIT should not be applied if temperature is below 10°C or above 35°C.

CLEAN UP

Clean up wet **ACRABIT** deposits with water and dry **ACRABIT** deposits with **MARCMOVE**.

STORAGE

Store **ACRABIT** in sealed containers under cover in a cool area away from foodstuffs.

PACK SIZES

ACRABIT is sold in packs of 20 litres.

TRANSPORT

ACRABIT is a waterborne product and not in the hazardous goods category. It should not be transported next to food items.

FACTORY
16 GOONGARRIE STREET
BAYSWATER WA 6053
AUSTRALIA

POSTAL
PO BOX 385
BAYSWATER WA 6933
AUSTRALIA

TELEPHONE
TEL. (08) 9378 2022
FAX. (08) 9377 2575
MOB. 0408 940 669

IDENTIFICATION
PAGE 1 of 1
ISSUE: JULY 2017
REF: ACBT

QUINDALUP HOLDINGS PTY LTD (A.C.N. 009 026 386) AS TRUSTEE FOR CALMARC FAMILY TRUST (ABN 18 340 289 669)

This information is offered solely for the customer and/or specifier for their consideration, investigation and verification. The suggestions mentioned herein should be fully assessed prior to application. No warranty or implied liability is given for any recommendations, advice, suggestions made by Calmarc Chemicals or representatives, agents or distributors for the conditions of use and labour for the products which are beyond our control. Catalogue or specification contents may change from time to time without notice. M.S.D.S. is available.