

# DAMP-PEL RTU



## DESCRIPTION

**DAMP-PEL RTU (Ready to Use)** is an aqueous emulsion which is used to make mineral building materials damp-proof and water repellent.

## APPLICATIONS

- Injection into building foundations at or below floor level to form a damp course.
- Making plasterboard repellent.
- Making fired clay and concrete products water repellent.

## DIRECTIONS: WATER REPELLENT

Apply two coats of **DAMP-PEL RTU** as a wet-on-wet application. Spread rate of dilution should be 3-4m<sup>2</sup> per litre per coat.

Drying time for water repellency application is 4-6 hours at 25°C.

**DAMP-PEL RTU** should not be applied in rain or if inclement weather is expected within 72 hours.

## HANDLING & SAFETY

**DAMP-PEL RTU** should be kept away from glass or metals.

**NOTE:** A white deposit may form on the substrate surface if applied in excess.

## TRANSPORT

**DAMP-PEL RTU** is not classified as a dangerous or hazardous good under the guidelines of Safe Work Australia.

FACTORY  
16 GOONGARRIE STREET  
BAYSWATER WA 6053  
AUSTRALIA

POSTAL  
PO BOX 385  
BAYSWATER WA 6933  
AUSTRALIA

TELEPHONE  
TEL. (08) 9378 2022  
FAX. (08) 9377 2575  
MOB. 0408 940 669

IDENTIFICATION  
PAGE 1 of 1  
ISSUE: JAN 2024  
REF: DMPLR

QUINDALUP HOLDINGS PTY LTD (A.C.N. 009 026 386) AS TRUSTEE FOR CALMARC FAMILY TRUST (ABN 18 340 289 669)

This information is offered solely for the customer and/or specifier for their consideration, investigation and verification. The suggestions mentioned herein should be fully assessed prior to application. No warranty or implied liability is given for any recommendations, advice, suggestions made by Calmarc Chemicals or representatives, agents or distributors for the conditions of use and labour for the products which are beyond our control. Catalogue or specification contents may change from time to time without notice. S.D.S. is available.