

DYNAMIC



DESCRIPTION

DYNAMIC is a multipurpose cleaner that does not contain solvents, caustics or conventional additives which standard cleaners have. **DYNAMIC** is designed to be biologically and environmentally safe. **DYNAMIC** has the ability to remove many types of stains off a variety of surfaces.

APPLICATIONS

DYNAMIC is used to remove stains from surfaces such as concrete, clay and concrete paving, ceramic tiles, grout, industrial painted surfaces (factory floors), shower doors and vinyl sheet as examples.

DIRECTIONS

DYNAMIC should at all times be trialed on a small section of surface to be cleaned to evaluate its performance or any harmful effect on the surface.

DYNAMIC can be infinitely diluted with water. For most purposes, **DYNAMIC** is diluted between 4 and 9 times with water. If in doubt, trial dilutions on an inconspicuous area before commencing full clean.

GENERAL EXTERNAL SURFACES: For most applications, wet the surface to be cleaned with water. While the surface is still wet, spray on an even layer of **DYNAMIC**. Brush the **DYNAMIC** over the area then high-pressure water blast the surface to remove **DYNAMIC** and associated stains.

GENERAL INTERNAL SURFACES: For most applications, a clean wetted (but not saturated) rag can be used. Spray **DYNAMIC** onto surface. Wipe surface until stain is removed then use either a wet/dry vacuum or rinse with water then dry with clean, dry cloth. Depending on the amount of **DYNAMIC** used, a second rinse with water may be necessary.

GROUTS/TILES: Spray on to the surface and using a wet, stiff nylon brush, scrub surface liberally. Wet/dry vacuum or rinse with water then dry with clean, dry cloth.

SHOWER SCREENS: Spray **DYNAMIC** over the shower screen and wipe in a circular motion using a wet non-abrasive sponge or clean wetted rag. Wipe until stain disappears then rinse down with water. Leave to dry. Screen can be rinsed down whilst in a running shower.

PAINTED SURFACES: **DYNAMIC** can be diluted 1 to 2 times with water for this application. Follow **GENERAL EXTERNAL SURFACES** but water blast with low pressure or hose. Always perform sample tests on paint work before proceeding.

If any surface dries out during application or brooming of the **DYNAMIC**, re-wet the surface and continue.

CLEAN UP

Clean up or removal of **DYNAMIC** is done with water.

STORAGE

Store all products under cover, in a cool area, away from foodstuffs, with lids on when not in use.

PACK SIZES

DYNAMIC is sold in packs of 1 litre, 5 litres, 20 litres and 200 litres

TRANSPORT

DYNAMIC is a hazardous good as defined by Safe Work Australia.

FACTORY
16 GOONGARRIE STREET
BAYSWATER WA 6053
AUSTRALIA

POSTAL
PO BOX 385
BAYSWATER WA 6933
AUSTRALIA

TELEPHONE
TEL. (08) 9378 2022
FAX. (08) 9377 2575
MOB. 0408 940 669

IDENTIFICATION
PAGE 1 of 1
ISSUE: JULY 2011
REF: DYMC

QUINDALUP HOLDINGS PTY LTD (A.C.N. 009 026 386) AS TRUSTEE FOR CALMARC FAMILY TRUST (ABN 18 340 289 669)
This information is offered solely for the customer and/or specifier for their consideration, investigation and verification. The suggestions mentioned herein should be fully assessed prior to application. No warranty or implied liability is given for any recommendations, advice, suggestions made by Calmarc Chemicals or representatives, agents or distributors for the conditions of use and labour for the products which are beyond our control. Catalogue or specification contents may change from time to time without notice. S.D.S. is available.