

EXUTA LIQUID MASK



DESCRIPTION

EXUTA LIQUID MASK is a **GLASS CLEAR FLEXIBLE** Waterborne Protective Acrylic Membrane. **EXUTA LIQUID MASK** is applied to the glass and new aluminium frames in windows to give protection to the windows from building debris during the building process. After which it is then peeled off leaving a clean window glass and frame.

FEATURES

EXUTA LIQUID MASK forms a glass clear film allowing to view clearly through to what is on the other side of the glass pane.

EXUTA LIQUID MASK is able to be applied to other substrates, e.g. glazed ceramic tiles, smooth flat painted steel. The substrates need to be totally non-porous and smooth and very hard throughout.

EXUTA LIQUID MASK is able to be used as a temporary water-resistant membrane.

PRECAUTIONS: EXUTA LIQUID MASK is best tested on a substrate required to be protected temporary to observe if the product is fit for the particular substrate it is applied to.

APPLICATION

EXUTA LIQUID MASK can be applied by a long bristle brush, airless spray or a short bristle (hair) 2-4 mm on a roller. Apply a thin film primer coat over the area to be coated. This will dry reasonably quickly. Apply a full coat over the primer at the required spread rate to give a finish glass clear dry film. Use a table following as a guide to the dry film thickness and wet film coverage necessary to achieve the dry film thickness. Usual application of the wet film is 2.0-2.5 m²/litre.

The wet film usually dries externally in summer conditions in 1.5 hours touch dry and up to 3 hours for touch dry in winter conditions.

Full dry externally as a guide is 24-48 hours. Internally these times may be the same for similar weather conditions, but generally it is longer.

REMOVAL

Lift an edge of the coating using a fingernail or a square flat rectangular spatula can be pushed along the glass to the coating edge to lift and form a ridge which can be finger grasped to begin the pulling.

CLEAN UP

In the wet state clean off with a rag or water. In the dry state, peel off.

STORAGE

EXUTA LIQUID MASK is stored under cover with lid tightly pressed on between 5°C-30°C. If the product skins, the dried surface skin can be removed and the liquid remainder used as normal.

SAFETY

EXUTA LIQUID MASK is neutral to slightly alkaline. Wear eye goggles, gloves and protective clothing when using or handling the product.

PACK SIZES

EXUTA LIQUID MASK is sold in containers of 5, 10, 15 and 20 litres.

TRANSPORT

EXUTA LIQUID MASK is not classified as dangerous or hazardous for transport by Safe Work Australia.

FACTORY
16 GOONGARRIE STREET
BAYSWATER WA 6053
AUSTRALIA

POSTAL
PO BOX 385
BAYSWATER WA 6933
AUSTRALIA

TELEPHONE
TEL. (08) 9378 2022
FAX. (08) 9377 2575
MOB. 0408 940 669

IDENTIFICATION
PAGE 1 of 1
ISSUE: JUNE 2020
REF: EXLM

QUINDALUP HOLDINGS PTY LTD (A.C.N. 009 026 386) AS TRUSTEE FOR CALMARC FAMILY TRUST (ABN 18 340 289 669)

This information is offered solely for the customer and/or specifier for their consideration, investigation and verification. The suggestions mentioned herein should be fully assessed prior to application. No warranty or implied liability is given for any recommendations, advice, suggestions made by Calmarc Chemicals or representatives, agents or distributors for the conditions of use and labour for the products which are beyond our control. Catalogue or specification contents may change from time to time without notice. S.D.S. is available.