

GRAFFI PAINT REMOVER



DESCRIPTION

GRAFFI PAINT REMOVER is a relatively safe, solvent blend with about ten percent of Potassium Hydroxide dissolved in it. The product is designed specifically to be quick acting on spray can graffiti for fast removal from mineral substrates or most forms of painted substrate.

FEATURES

- **GRAFFI PAINT REMOVER** is excellent for removing graffiti from unpainted sandstone, limestone, clay brickwork, concrete, concrete block, various stone and granite materials.
- **GRAFFI PAINT REMOVER** has the ability to remove graffiti on most types of painted substrates. In some cases, dark coloured painted substrates may discolour slightly where the graffiti has been removed to the surrounds.
- **GRAFFI PAINT REMOVER** is relatively safe to use.
- **GRAFFI PAINT REMOVER** is fast acting with the removal action on graffiti.

DIRECTIONS

Apply a liberal coat of **GRAFFI PAINT REMOVER** onto the graffiti using a nylon or polyester brush. About 1m² of graffiti can be done in one application. For difficult, thick, heavy applications of graffiti, another 2-3 applications of **GRAFFI PAINT REMOVER** will be necessary. The process per unit area described above is done in about 3-5 minutes. Use a high-pressure water blaster (preferably hot water) to blast off the loosened graffiti.

Repeat process if any small traces of graffiti are remaining. If removing graffiti by hand after applying the remover, remove the graffiti using a stiff nylon brush with copious quantities of running water directed at the area of scrubbing.

CAUTION

- Do not allow the applied **GRAFFI PAINT REMOVER** to dry out after application.
- Do not use steel or stainless-steel brushes as they damage the surface of the substrates.
- If the substrates are very hot, pre-wet with water, allow to nearly dry and proceed with application and removal as above
- Keep the product away from aluminium, copper and brass as these metals react to caustic chemicals e.g. Potassium Hydroxide.

FIRST AID

SWALLOWED: Immediately rinse mouth with water. Do not induce vomiting. If vomiting occurs give further water. Seek immediate medical advice.

EYE: Immediately irrigate with copious amounts of water for at least 15 minutes. Hold eyelids open while rinsing. Wash skin area and transport patient to hospital or a medical centre.

SKIN: Immediately wash contaminated skin area with plenty of water. Remove contaminated clothing and wash if being reused. If redness, blistering or irritation occurs, seek medical advice.

INHALED: Remove patient from contaminated area. Loosen clothing. Keep patient warm and relaxed until full recovery. If breathing laboured and patient is experiencing cyanosis, ensure airways are clear and have a trained person give oxygen through a face mask. If breathing stopped, apply artificial respiration. If cardiac arrest occurs apply external cardiac massage. Seek medical advice if symptoms persevere.

CLEAN UP

Wash down with water. Restrict any product flowing down drains or into rivers. Absorb any wet residue with absorbents such as attapulgate or vermiculite. Dispose in a recognised waste site.

FACTORY
16 GOONGARRIE STREET
BAYSWATER WA 6053
AUSTRALIA

POSTAL
PO BOX 385
BAYSWATER WA 6933
AUSTRALIA

TELEPHONE
TEL. (08) 9378 2022
FAX. (08) 9377 2575
MOB. 0408 940 669

IDENTIFICATION
PAGE 1 of 2
ISSUE: JULY 2011
REF: GPAR

QUINDALUP HOLDINGS PTY LTD (A.C.N. 009 026 386) AS TRUSTEE FOR CALMARC FAMILY TRUST (ABN 18 340 289 669)
This information is offered solely for the customer and/or specifier for their consideration, investigation and verification. The suggestions mentioned herein should be fully assessed prior to application. No warranty or implied liability is given for any recommendations, advice, suggestions made by Calmarc Chemicals or representatives, agents or distributors for the conditions of use and labour for the products which are beyond our control. Catalogue or specification contents may change from time to time without notice. S.D.S. is available.

GRAFFI PAINT REMOVER



SAFETY

Wear rubber (short term use) or nitrile gloves (long term use) face shield or safety goggles. In low ventilation areas use a half face mask with and organic absorbent cartridge. Externally it is wise to do the same. Keep the product away from oxidising agents and acids.

PACK SIZES

GRAFFI PAINT REMOVER is sold in packs of 5, 10 and 20 litres.

TRANSPORT

Shipping Name: Corrosive Liquid, N.O.S

Dangerous Goods Code: 8

Subsidiary Risk: 3

UN No.: 2920

Packaging Group: II or III

I.E.R.G No.: 18

HAZCHEM: 2x

FACTORY
16 GOONGARRIE STREET
BAYSWATER WA 6053
AUSTRALIA

POSTAL
PO BOX 385
BAYSWATER WA 6933
AUSTRALIA

TELEPHONE
TEL. (08) 9378 2022
FAX. (08) 9377 2575
MOB. 0408 940 669

IDENTIFICATION
PAGE 2 of 2
ISSUE: JULY 2011
REF: GPAR

QUINDALUP HOLDINGS PTY LTD (A.C.N. 009 026 386) AS TRUSTEE FOR CALMARC FAMILY TRUST (ABN 18 340 289 669)

This information is offered solely for the customer and/or specifier for their consideration, investigation and verification. The suggestions mentioned herein should be fully assessed prior to application. No warranty or implied liability is given for any recommendations, advice, suggestions made by Calmarc Chemicals or representatives, agents or distributors for the conditions of use and labour for the products which are beyond our control. Catalogue or specification contents may change from time to time without notice. S.D.S. is available.