MATERIAL SAFETY DATA SHEET Page 1 of 6
Product: FIBRETAK Date of Issue: 26 January 2019



CALMARC CHEMICALS

MANUFACTURING INDUSTRIAL CHEMISTS

16 GOONGARRIE ST, BAYSWATER W.A 6053.

TELEPHONE : Bus. (08) 93782022 Mobile 0418 956 860 A/H (08) 9381 5052. Facsimile (08) 9377 2575 A.C.N 009 026 386. ABN 18 340 289 669

THIS PRODUCT IS NOT A HAZARDOUS SUBSTANCE AS DEFINED BY SAFE WORK AUSTRALIA

SECTION 1 – CHEMICAL PRODUCT AND COMPANY INFORMATION

Product Name: FIBRETAK Manufacture Code: FBTK

Emergency Telephone No: (08) 9378 2022

0408 940 669 (08) 9381 5052

Email: accounts@calmarc.com.au

Creation Date: 16 June 2003

SDS Responsibility: Calmarc Chemical's Technical Sales (08) 9378 2022

0408 940 669

Other Information: This SDS summarises our best knowledge of the health and

safety hazard information of the product and how to safely handle and use the product in the workplace. Each user should read this SDS and consider the information in the context of how the product will be handled and used in the workplace including in conjunction with other products. If clarification of further information is needed to ensure that an appropriate risk assessment can be made, the user should contact this company. Our responsibilities for products sold are subject to our standard terms and conditions. A copy of our terms and conditions and technical information pamphlets are available upon request.

DISCLAIMER

This information is based on the present level of knowledge about safety requirements not specific properties. The listed data is therefore subject to change and revision without notice and cannot be guaranteed. No warranty expressed or implied is made as to accuracy, reliability or completeness of the detail in this document.

SECTION 2 - HAZARDS INFORMATION/EMERGENCY OVERVIEW

Globally Harmonised System

Hazard Classification Not hazardous according to the criteria of the Globally Harmonised

System of classification and labelling of Chemicals (GHS).

Hazard Category None allocated.

Physical Data Product is water based.

Use Adhesive resin for adhering fibreglass mat to concrete, plaster,

timber and prime coated metal. The FIBRETAK/fibreglass is then tiled or screeded on, or overcoated with ATTAFLEX or FLEXITEX

for a waterproofing membrane.

Directions Place a layer of FIBRETAK onto the substrate. Lay the fibreglass

into the wet resin. Apply a coat of FIBRETAK over laid fibreglass

and allow to dry clear before further treatments.

MATERIAL SAFETY DATA SHEET Page 2 of 6
Product: FIBRETAK Date of Issue: 26 January 2019



CALMARC CHEMICALS

MANUFACTURING INDUSTRIAL CHEMISTS

16 GOONGARRIE ST, BAYSWATER W.A 6053.

TELEPHONE : Bus. (08) 93782022 Mobile 0418 956 860 A/H (08) 9381 5052. Facsimile (08) 9377 2575 A.C.N 009 026 386. ABN 18 340 289 669

ACUTE HEALTH EFFECTS

Swallowed Effects unknown. Small quantities (a few mls) is unlikely to cause

more than temporary discomfort.

Eye Strong irritant. May cause damage to the eyes on prolonged

exposure due to small residual of sodium hydroxide present.

Skin May cause irritation. Repeated exposure may cause dermatitis to

susceptible individuals due to degreasing effect of the surfactants

present.

Inhalation Possible nausea due to small amounts of styrene butadiene dimer.

Chronic None known at this time.

SPECIAL HEALTH EFFECTS

Environmental Do not allow products to enter drinking water, rivers and streams

as it may harm vegetation and wildlife.

SECTION 3 - COMPOSTION/INFORMATION ON INGREDIENTS

INGREDIENTSCAS No.CONCENTRATIONSBR Copolymer30-60%Water7732-18-530-60%Other compounds and/or impuritiesto make 100%

SECTION 4 - FIRST AID MEASURES

Swallowed For a conscious patient, rinse the mouth with water and give

plenty of water to drink. Never give a drink to an unconscious

person.

Eye Flush eyes with copious amounts of water for 15 minutes with

eyes open.

Skin Wash off with soap and water. Remove any contaminated

clothing.

Inhalation Remove to fresh air.

Advice to Doctor Treat as for polymerised acrylic resins dispersed in water in the

form of an emulsion or treat symtomatically.

SECTION 5 – FIRE FIGHTING MEASURES

Fire and Explosion Wear self-contained breathing apparatus to avoid inhalation toxic

smoke or fumes.

VentilationLocal exhaust and ventilation is recommended if used internally.

Externally, normal air movement is usually sufficient.

MATERIAL SAFETY DATA SHEET Page 3 of 6
Product: FIBRETAK Date of Issue: 26 January 2019



CALMARC CHEMICALS

MANUFACTURING INDUSTRIAL CHEMISTS

16 GOONGARRIE ST, BAYSWATER W.A 6053.

TELEPHONE: Bus. (08) 93782022 Mobile 0418 956 860 A/H (08) 9381 5052. Facsimile (08) 9377 2575 A.C.N 009 026 386. ABN 18 340 289 669

Earth the product container if there is a potential for state

electricity build up.

Autoignition TemperatureOnly ignites in the presence of a very strong ignition source and

only after the water is removed.

Source of Ignition Keep away from open flame, sparks, high sources of heat

transmission and static electricity discharge.

Flash Point Not applicable – aqueous product.

Extinguishing MediaUse carbon dioxide, dry chemical or B.C.F. fire extinguishers.

Special Fire

Fighting Procedures

None

Decomposition ProductsCarbon monoxide, carbon dioxide, styrene gases and vapours.

Hazardous polymerisation will not occur.

Upper Explosive Limit N/A
Lower Explosive Limit N/A

Reactivity Product may coagulate if in contact with flocculants, e.g. organic

solvents and/or salt solutions.

Protection of Firefighters Wear safety boots, non-flammable overalls, gloves, safety hat

(with face shield) or firefighter helmet (preferred), goggles and self-contained breathing apparatus. All skin areas should be covered. Block all drains and water courses to inhibit any spillage

into them.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Spills and Disposal Spills should be contained and absorbed with sand, vermiculite,

attapulgite or inert material. Place the contaminated material in a plastic or metal container and dispose of it at an industrial waste site. Do not allow the product to enter drains or waterways. Small

amounts can cause high turbidity.

Cleaning Protection Open up the area where spill or leak has occurred to ventilate

direct vapours away.

Attach earth leak cables to any containers in the spill area. Have absorbents, such as vermiculate, attapulgite, carboard or sand on hand to control flow of the spilled mobile product. Use wet

vacuum cleaner or mop to collect any small spills.

SECTION 7 – HANDLING AND STORAGE

Protection against explosions and fires

Keep containers on site away from sources of heat, sparks and earth if necessary, for static electricity. Use secure locked storage if possible and have forced or natural ventilation over worksite or storage areas.

MATERIAL SAFETY DATA SHEET

Page 4 of 6

Product: FIBRETAK

Date of Issue: 26 January 2019



CALMARC CHEMICALS

MANUFACTURING INDUSTRIAL CHEMISTS

16 GOONGARRIE ST, BAYSWATER W.A 6053.

TELEPHONE : Bus. (08) 93782022 Mobile 0418 956 860 A/H (08) 9381 5052. Facsimile (08) 9377 2575 A.C.N 009 026 386. ABN 18 340 289 669

Packages The product is supplied in high density polypropylene bottles,

jerry cans or cubes. Packaging group type II and III.

Storage After decanting from containers, tightly reseal containers and

store immediately. Store away from food stuffs. Store in a cool, dry, well-ventilated area under cover between 5°C and 30°C. Store containers away from any heat sources, sparks. Do not

store with oxidising agents or acids.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Measures Apply in a well-ventilated area either externally or internally.

Airborne Exposure Limits No airborne exposure limits have been established. A blanket

limit of 10 mg/m³ for dusts or mists is used in thes cases.

PERSONAL PROTECTIVE EQUIPMENT

Eye/Face Protection Wear safety glasses, goggles or preferably a face shield. In

enclosed non-ventilated areas, an air line to full head cover helmet with mask may be necessary. Breathing mask to be

suitable for organic vapours.

Skin/Body Protection Wear vinyl, latex or PVC gloves for 8-hour day. Short-term

protection (1 hour), natural rubber is suitable. Wear full coverall

clothing protection with safety boots.

Hygiene Measure Wash hands before meal breaks and at the end of a work period.

Any contaminated clothing should be removed. Avoid inhaling any

fumes on a long-term basis.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Substance Formulation of chemicals Physical Form Medium viscosity liquid

Colour Milky white

Odour Slightly pungent at close proximity

pH 8-10

Boiling Point 100°C at 760 mmHg
Melting Point Not Applicable
Flash Point Not Applicable

Freezing Point 0°C

Autoignition Only ignites in the presence of a very strong ignition source and

only after the water is removed.

Water Solubility Miscible in liquid form. Insoluble as a dried film.

Specific Gravity 1.05 g/cc Corrosivity Not Corrosive MATERIAL SAFETY DATA SHEET Page 5 of 6
Product: FIBRETAK Date of Issue: 26 January 2019



CALMARC CHEMICALS

MANUFACTURING INDUSTRIAL CHEMISTS

16 GOONGARRIE ST, BAYSWATER W.A 6053.
TELEPHONE : Bus. (08) 93782022 Mobile 0418 956 860 A/H (08) 9381 5052.
Facsimile (08) 9377 2575 A.C.N 009 026 386. ABN 18 340 289 669

SECTION 10 - STABILITY AND REACTIVITY

Stability Stable as supplied at normal (average) atmospheric temperatures.

Reactivity Product may coagulate if in contact with floculants, for example,

organic solvents and/or solvent solutions.

Decomposition ProductsCarbon monoxide, carbon dioxide, nitrogen gases and vapours.

Hazardous polymerisation will not occur.

SECTION 11 – TOXICOLOGICAL INFORMATION

None Known.

SECTION 12 – ECOLOGICAL INFORMATION

None Known.

SECTION 13 – DISPOSAL CONSIDERATIONS

Waste Disposal Allow absorbents to dry out in the open atmosphere.

Contaminated product should be reprocessed by an approved organisation. Place any dried absorbent in plastic bags, seal and

dispose at an approved site.

SECTION 14 – TRANSPORT INFORMATION

Shipping Name Fibretak

Other Names Synthetic Copolymer

Dangerous Goods Code

Subsidiary Risk

UN Number

Packaging Group

I.E.R.G. No.

HAZCHEM

None

None

SECTION 15 – REGULATORY INFORMATION

None Known.

SECTION 16 – OTHER INFORMATION

The details in this document are based on the state of our knowledge at the time of revision. They do not constitute an assurance of the described product properties in terms of statutory warranty requirements.

The providing of this document to a recipient does not relieve the recipient of his or her responsibility toward compliance with all laws and stipulations applicable to the product.

MATERIAL SAFETY DATA SHEET
Page 6 of 6
Product: FIBRETAK
Date of Issue: 26 January 2019



CALMARC CHEMICALS

MANUFACTURING INDUSTRIAL CHEMISTS

16 GOONGARRIE ST, BAYSWATER W.A 6053.
TELEPHONE: Bus. (08) 93782022 Mobile 0418 956 860 A/H (08) 9381 5052.
Facsimile (08) 9377 2575 A.C.N 009 026 386. ABN 18 340 289 669

Directions for use are on the label and brochure describing Fibretak.

SDS NEXT REVIEW DATE 26 January 2024

END OF SDS FOR FIBRETAK